

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
21 February 2002 (21.02.2002)

PCT

(10) International Publication Number  
**WO 02/14535 A2**

(51) International Patent Classification<sup>7</sup>: **C12Q 1/00**

(21) International Application Number: PCT/GB01/03615

(22) International Filing Date: 13 August 2001 (13.08.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0019694.9 11 August 2000 (11.08.2000) GB

(71) Applicant (for all designated States except US): **CAMBRIDGE SENSORS LIMITED** [GB/GB]; Downhams House, Downhams Lane, Cambridge CB4 1XT (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **YON-HIN, Bernadette** [GB/GB]; Cambridge Sensors Limited, Downhams House, Downhams Lane, Cambridge CB4 1XT (GB). **MCCANN, James** [GB/GB]; Cambridge Sensors Limited, Downhams House, Downhams Lane, Cambridge CB4 1XT (GB).

(74) Agent: **GILL JENNINGS & EVERY**; Broadgate House, 7 Eldon Street, London EC2M 7LH (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SI, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— without international search report and to be republished upon receipt of that report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: **ELECTROCHEMICAL STRIP TEST FOR SMALL VOLUMES**

(57) Abstract: A device for the electrochemical detection of an analyte in a sample, comprises electrodes and appropriate reagents on a substrate defining a volume within which the sample can be detected, wherein said volume is 500 nL or less.



**WO 02/14535 A2**

## ELECTROCHEMICAL STRIP TEST FOR SMALL VOLUMES

### Field of the Invention

This invention relates to an electrochemical test cell for the measurement of reactive species. Such a sensor can be used for the measurement of enzymes, enzyme substrates, cofactors or mediators. One particular application is the measurement of glucose for use in diabetes.

### Background of the Invention

Diabetes mellitus is the most common endocrine disease and affects between 3-8% of the population. Various studies, such as the UK Prospective Diabetes Study (UKPDS, Lancet, 12th September 1998) have pointed out the importance of maintaining a normal glucose level in the blood or plasma, in order to delay the onset of diabetic complications.

Many diabetics monitor their disease by a regime of tests at home. A simple means of monitoring their disease is therefore desirable.

Electrochemical strip tests for glucose, electrolytes, lipids and enzymes have all been widely discussed in the patent and other literature. For example, US-A-4224125 discloses an enzyme electrode system in which an enzyme such as glucose oxidase is used to sense glucose. US-A-5820551 discloses such a strip electrode fabricated by screen printing.

### Summary of the Invention

The present invention is based on the realisation that, by using appropriate chemistry etc, an adequate signal can be achieved if a cavity is provided that is smaller than has previously been used, i.e. which holds 500 nL or less of blood. In particular, the invention allows the detection of glucose in whole blood, using a simple to use strip test, characterised in that the volume of sample required is very small, e.g. less than 200 nL and down to 50 nL.

In most respects, a device of the invention can be made from known materials. However, it has been found that its size can be reduced, because sufficient current density can be achieved that there is adequate sensitivity for the analyte, typically 90-100 nA/mM glucose.

The small volume of blood that can be utilised in the invention means that the sample can be taken from a part of the body having a low vasculature. Thus, for example, the sample can be taken from the arm.

#### Brief Description of the Drawings

5            Figures 1 to 3 of the drawings are each associated plan and side views of different illustrative embodiments of the invention. The drawings show a cell or sample area 1, a cover 2, a spacer layer 3, a reference/counter electrode 4, a working electrode 5, a cell-defining layer 6, a counter electrode 7, a reference electrode 8, and a strip/sample electrode 9.

#### 10    Description of the Invention

          Electrochemical strips for the detection of glucose in whole blood typically comprise an working, reference and counter electrode, or combination thereof, for the detection and quantitation of the activity of reagents or reaction products on the strip. Examples of these reagents may include enzymes, enzyme  
15    products or mediators accepting electrons from redox enzymes on the strip.

          The electrodes are preferably printed or deposited onto an elongate substrate, configured for ease of use by the diabetic and for insertion into a reader. Such a substrate may also include other tests of use for the diabetic such as, but not limited to, glycosylated haemoglobin, glucose and potassium.  
20    Some of the reagents may be deposited directly onto the electrodes themselves or onto other structures incorporated in the device, including wetting meshes such as is known in the art. The mesh is preferably as described in WO-A-00/28068. The use of a mesh in the cavity, e.g. having an open area of about 30%, can reduce the sample volume.

25            Appropriate reagents may be placed on the electrochemical strip test by methods including, but not limited to, screen printing and dosing the enzymes or enzyme-mediator couples. Especially for the detection of glucose, such reagents may be, for example:

          glucose oxidase and ferrocene/ferricyanide  
30            glucose oxidase and oxygen to yield hydrogen peroxide  
          glucose dehydrogenase and ferricyanide  
          glucose dehydrogenase and NAD and Meldola's Blue

The effect of interferents in the test may be reduced by including enzymes or chemicals to reduce ascorbate interference, e.g. ascorbate oxidase. Haematocrit interference may be reduced by including saponin, digitonin, or other lysing agents.

- 5           PVP, PVA and other polymers may be included, to increase linearity. Surfactants may be added to the device, to aid filling.

- The assay may also incorporate features such as filling via the side of the elongate substrate, to assist the diabetic in using the device. This is described in WO-A-00/28086 and also WO-A-98/55856 (the contents of both of which are  
10 incorporated herein by reference).

The output from the device may also be quantitated on small electronic instrument. Analysis of the output from the device may be *via* coulometry, amperometry, analysis or cyclic voltamogram or other electrochemical analytical methods known in the art.

- 15           The arrangement of the device may include provision for the sequential exposure of reagents to the sample, to allow the reactions to proceed in a sequential or time-delayed manner, to optimise the readout.

- In a typical configuration that embodies the invention, the device comprises two electrodes placed approximately 100  $\mu\text{m}$  or more apart: a  
20 counter/reference electrode preferably made of Ag/AgCl and a second conductor of either Au, Pt, Pt/C or C. A well is constructed by laminating a plastics layer around the cell or printing a layer around the cell, as shown in Figure 1. A top cover may then be added to complete the cell. The electrodes are approximately 100  $\mu\text{m}$  wide and 1000  $\mu\text{m}$  long. Before laminating the top cover onto the  
25 system, the reagents are dosed onto the device. Strips made with a Au, Pt or Pt/C conductor may contain glucose oxidase. Hydrogen peroxide is detected electrochemically on the strip. Strips made of a carbon conductor may contain a redox enzyme (glucose oxidase or glucose dehydrogenase) and a mediator for the enzyme (potassium ferricyanide or phenoxazines including Meldola's Blue).

- 30           In a second embodiment of the invention, a device comprises 3 conducting electrodes, namely a working electrode (carbon, Pt, Au or Pt/C), a reference electrode made of Ag/AgCl and a counter electrode (C, Pt, Au or Pt/C),

as shown in Figure 2. The reagents, i.e. enzyme, cofactor and mediator, are deposited on the working electrode as a single or multiple layers. Alternatively, the reagents are dried over the whole of the cell. A channel is created over the reagents by laminating a thin plastic layer or printing a layer of adhesive around the cell. A clear cover with an air exit hole is placed over the device to complete the test strip. The cell volume can be further reduced by sandwiching a mesh layer between the substrate containing the conducting electrodes and reagents and the cover.

In a third embodiment of the invention, a device comprises 3 conducting electrodes, namely a working electrode (carbon, Pt, Au or Pt/C), a reference/counter electrode made of Ag/AgCl and a strip/sample detection electrode (C, Pt, Au or Pt/C), as shown in Figure 3. The reagents, i.e. enzyme, cofactor and mediator, are deposited on the working electrode as a single or multiple layers. Alternatively, the reagents are dried over the whole of the cell. A channel is created over the reagents by laminating a thin plastic layer or printing a layer of adhesive around the cell. A clear cover with an air exit hole is placed over the device to complete the test strip. Again, the cell volume can be further reduced by sandwiching a mesh layer between the substrate containing the conducting electrodes and reagents and the cover.

CLAIMS

1. A device for the electrochemical detection of an analyte in a sample, which comprises electrodes and appropriate reagents on a substrate defining a volume within which the sample can be detected, wherein said volume is 500 nL  
5 or less.
2. A device according to claim 1, wherein the volume is 50 to 200 nL.
3. A device according to claim 1 or claim 2, wherein the analyte is glucose.
4. A device according to claim 3, wherein the reagents comprise glucose oxidase.
- 10 5. A device according to claim 3, wherein the reagents comprise glucose dehydrogenase.
6. A device according to claim 4, wherein the reagents comprise ferrocene/ferricyanide.
7. A device according to claim 5, wherein the reagents comprise  
15 ferricyanide.
8. A device according to claim 5, wherein the reagents comprise NAD and Meldola Blue.
9. A method for the electrochemical detection of an analyte in a sample, which comprises introducing the sample into the cavity of a device according to  
20 any preceding claim, and detecting the current.
10. A method according to claim 9, wherein the sample is whole blood.

Figure 1




Figure 2





Figure 3





(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
21 February 2002 (21.02.2002)


PCT

(10) International Publication Number  
**WO 02/14535 A3**

- (51) International Patent Classification<sup>7</sup>: **G01N 27/327**, C12Q 1/00
- (21) International Application Number: **PCT/GB01/03615**
- (22) International Filing Date: **13 August 2001 (13.08.2001)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
0019694.9      11 August 2000 (11.08.2000)      **GB**
- (71) Applicant (for all designated States except US): **CAMBRIDGE SENSORS LIMITED [GB/GB]**; Downhams House, Downhams Lane, Cambridge CB4 1XT (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **YON-HIN, Bernadette [GB/GB]**; Cambridge Sensors Limited, Downhams House, Downhams Lane, Cambridge CB4 1XT (GB). **MCCANN, James [GB/GB]**; Cambridge Sensors Limited, Downhams House, Downhams Lane, Cambridge CB4 1XT (GB).
- (74) Agent: **GILL JENNINGS & EVERY**; Broadgate House, 7 Eldon Street, London EC2M 7LH (GB).
- (81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.**
- (84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM). European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR). OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).**
- Published:**  
— with international search report

[Continued on next page]

(54) Title: **ELECTROCHEMICAL STRIP TEST FOR SMALL VOLUMES**



(57) Abstract: A device for the electrochemical detection of an analyte in a sample, comprises electrodes and appropriate reagents on a substrate defining a volume within which the sample can be detected, wherein said volume is 500 nL or less.



(88) Date of publication of the international search report:  
13 June 2002

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 01/03615

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G01N27/327 C12Q1/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C12Q G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 98 35225 A (TOMASCO MICHAEL F ;HELLER ADAM (US); HELLER E & CO (US); SAY JAMES) 13 August 1998 (1998-08-13) the whole document ---	1-10
X	EP 0 964 059 A (MATSUSHITA ELECTRIC IND CO LTD) 15 December 1999 (1999-12-15) the whole document ---	1-10
X	WO 00 28068 A (CAMBRIDGE SENSORS LTD ;BLAIR NEIL (GB); COX LORNA JEAN (GB); MCCAN) 18 May 2000 (2000-05-18) the whole document ---	1-10
A	WO 97 02487 A (BOEHRINGER MANNHEIM CORP) 23 January 1997 (1997-01-23) abstract --- -/--	1

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

8 February 2002

Date of mailing of the international search report

15/02/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.  
Fax: (+31-70) 340-3016

Authorized officer

Moreno, C

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 01/03615

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 628 890 A (CARTER NIGEL F ET AL) 13 May 1997 (1997-05-13) abstract	1
A	WO 99 13101 A (ABBOTT LAB) 18 March 1999 (1999-03-18) abstract	1

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 01/03615

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9835225	A	13-08-1998	AU 6157898 A	26-08-1998
			EP 0958495 A1	24-11-1999
			JP 2000509507 T	25-07-2000
			WO 9835225 A1	13-08-1998
			US 6143164 A	07-11-2000
			US 6120676 A	19-09-2000
EP 0964059	A	15-12-1999	JP 11352093 A	24-12-1999
			CN 1243951 A	09-02-2000
			EP 0964059 A2	15-12-1999
WO 0028068	A	18-05-2000	AU 1063900 A	29-05-2000
			BR 9915211 A	30-10-2001
			CN 1326514 T	12-12-2001
			EP 1129211 A1	05-09-2001
			WO 0028068 A1	18-05-2000
WO 9702487	A	23-01-1997	US 5762770 A	09-06-1998
			AU 712527 B2	11-11-1999
			AU 6345196 A	05-02-1997
			CA 2224308 A1	23-01-1997
			DE 29623913 U1	07-09-2000
			DE 69617464 D1	10-01-2002
			DE 874984 T1	05-10-2000
			EP 0874984 A1	04-11-1998
			ES 2154250 T1	01-04-2001
			JP 2001511881 T	14-08-2001
			WO 9702487 A1	23-01-1997
US 5628890	A	13-05-1997	CA 2159553 A1	30-03-1997
			JP 9222411 A	26-08-1997
WO 9913101	A	18-03-1999	US 6129823 A	10-10-2000
			AU 9129998 A	29-03-1999
			BR 9812016 A	26-09-2000
			EP 1009850 A1	21-06-2000
			JP 2001516040 T	25-09-2001
			WO 9913101 A1	18-03-1999

**THIS PAGE BLANK (USPTO)**